for supplementary markings

INTRODUCTION:

Often safety signs are printed onto white plastic. Should the power fail, those signs are not visible in the dark and will not support building occupants during darkness emergencies.

PERMALIGHT® safety signs light up in the dark and show their message when all lights are out.

The below-shown Safety Signs are NOT code-compliant. For Building Code compliant EXIT Signs, inquire about PERMALIGHT® UL924-listed EXIT Signs and UL1994-listed Egress Path Markings Signs.

The below-shown NON-Building Code compliant Safety Signs are available in two material types:

» Easy peel-and-stick, self-adhesive film

Simply take off the paper backing and apply the signs to a smooth, clean surface. Also great on columns, pipes and similar curved surfaces.





Self-adhesive Film

Rigid PVC

» Durable rigid PVC, non-adhesive

These stiff, smooth signs work great on uneven, rough surfaces, even on brick wall. Attach with double-sided tape or Construction Adhesive (e.g., LiquidNails or Loctite from your local hardware store).

On the Shelf in these Designs:











NON-Building Code compliant LUMINANCE:

Photoluminescent Performance tested per German Standard DIN 67510:

Activation with 1000 Lux (93 foot-candles) of Xenon Lighting for 5 minutes:

the FILM Safety Signs have a guaranteed Luminance of at least

- 55 milli-candela per square meter (mcd/m²) after 10 minutes in full darkness, and
- 8 milli-candela per square meter (mcd/m²) after 60 minutes in full darkness.

the RIGID Safety Signs have a guaranteed Luminance of at least

- 20 milli-candela per square meter (mcd/m²) after 10 minutes in full darkness, and
- 3 milli-candela per square meter (mcd/m²) after 60 minutes in full darkness.

Photoluminescent Rigid PVC Background with Reflective EXIT Legend

ONE Sign with TWO Life Safety Effects:

- Photoluminescent Glow in the Dark when all lights are out
- Reflective shining back a Flashlight beam







Daylight Appearance







» Durable rigid PVC, non-adhesive

These stiff, smooth signs work great on uneven, rough surfaces, even on brick wall. Attach with double-sided tape or Construction Adhesive (e.g., LiquidNails or Loctite from your local hardware store).

Photoluminescent Performance tested per German Standard DIN 67510: Activation with 1000 Lux (93 foot-candles) of Xenon Lighting for 5 minutes: the RIGID Safety Signs have a guaranteed Luminance of at least

- 20 milli-candela per square meter (mcd/m²) after 10 minutes in full darkness, and
- 3 milli-candela per square meter (mcd/m²) after 60 minutes in full darkness.